
Jenfort Storage Water Heater

Product Catalogue





JN/JN(S Option)

總代理 Sole Agent



A-PLUS (HK) GROUP LTD. 愛家(香港)集團有限公司

www.aplusgroup.hk

Patent Pending HK16112201.2











香港葵涌青山公路403號匯城集團大廈5樓A-E室 Unit A-E, 5/F, Reason Group Tower, 403 Castle Peak Road, Kwai Chung, N.T., Hong Kong

電話Tel: (852) 3563 7238 傳真Fax: (852) 3563 8793

電郵Email: company@aplusgroup.hk

內置專利速熱系統 五分鐘快速加熱 大大延長熱水使用時間









X Rapid 5-minute heating

Built-in rapid heat storage system, it only takes 5 minutes to heat up, which is beyond imagination.

X Thermostat and overheat circuit breaker

All Zanussi electric water heaters adopt high-quality thermostat and overheat circuit breaker from France Cotherm to ensure precise temperature setting and product safety.

*** High efficiency heating tube**

High-quality Incoloy alloy heating tube is used to make the product more durable and efficient.

High-density insulation layer

A high-density synthetic resin insulation layer is used to maintain the water temperature in the inner tank, reduce heat loss, save energy, and achieve first-level energy efficiency.

X Special stainless steel inner tank

All inner tanks are made of special stainless steel. Because they are high-quality and durable, there is no need to worry about water leakage or deformation, so a 10-year warranty can be promised.

***** Automated welding

All Zanussi electric water heater inner tanks adopt fully automated welding technology to avoid human errors and stabilize product quality.

- **X** Automatic thermostat device
- **X Stable water outlet temperature**
- Splash protection
- **X** Awarded first-level energy label
- Product liability insurance HK\$10,000,000
- **% 2-year warranty for electrical parts**
- **X** 10-year warranty for inner tank

The first company in Hong Kong to obtain mandatory energy labeling







機電工程署 EMSD 符合機雷工程署安全規格











Won Q-Mark and multiple international safety certifications



JN Series		Single-Point Shower Unit			
Model	Capacity (Litres)	Size(mm) H W D	Power Rating (kW) 220 V	Net Weight (kg)	Net Weight Full Tank(kg)
JN-4	15	500 330 256	3/4	11	26
JN-5	18	563 330 256	3/4	12	30
JN-6	23	688 330 256	3/4	13	36
The above prod	ducts all come	ty Size(mm) Power Rating (kW) Net Weight Net Weight H W D 220 V (kg) Full Tank(kg) 500 330 256 3/4 11 26 563 330 256 3/4 12 30			

JN (S Option)

Shower type electric water heater with



Built-in patented rapid heating system, equipped with original environmentally friendly control components to regulate water flow; It can heat up to a comfortable temperature for rinsing within 5 minutes. Coupled with the Airjet environmentally friendly showerhead with first-level water efficiency, it achieves the best water supply effect.

> Airjet environmentally friendly showerhead Certified with first-level water efficiency label More water-saving









comfortable temperature



provide Long-lasting water supply with Oringinal Water-saving Aerator Showerhead



High Performance Heating Element



tempertaure can be preserved longer hence saving energy



Units range from 15 liters in volume,





throttle



Airjet environmentally friendly showerhead and mixer

The following is the comparison of opening water flow at the same time



JN(S Option	n)Series	Single-Point Shower Uni			
Model	Capacity (Litres)	Size(mm) H 闊W D	Power Rating (kW) 220 V	Net Weight (kg)	Net Weight Full Tank(kg)
JN-4(S Option)	15	500 330 256	3/4	11	26
JN-5(S Option)	18	563 330 256	3/4	12	30
JN-6(S Option)	23	688 330 256	3/4	13	36